



Italy
Climatizzatore ad alta efficienza e performance. Per i modelli da 12000 e 18000 BTU/h è disponibile anche una versione più compatta. Tutti i modelli sono dotati di un ventilatore a sette velocità regolabili, pompa scarico condensa e telecomando a infrarossi standard

France
Haute efficacité et le contrôle du climat de la performance. Pour les modèles 12000 et 18000 BTU/h est également une version plus compacte. Tous les modèles sont équipés d'un ventilateur réglable à sept vitesses, les drains de la pompe de condensat et télécommande infrarouge standard


UK
High efficiency and performance climate control. For models 12000 and 18000 BTU/h is also available a more compact version. All models are equipped with a seven-speed adjustable fan, condensate pump drains and standard infrared remote control

CASSETTE

MONOSPLIT DC INVERTER CASSETTE



UNITÀ ESTERNA - UNITÉ EXTÉRIEURE - OUTDOOR UNIT



600x600 mm



840x840 mm

UNITÀ INTERNA - UNITÉ INTÉRIEURE - INDOOR UNIT



Filocomando optional
 Commande mural optional
 Optional wire controller



Telecomando in dotazione
 Télécommande standard
 Standard Remote Control

CASSETTE MONOSPLIT DC INVERTER - CASK



Unità Monosplit Cassette Compact (600 x 600 mm)					
Unità Interna - Unité intérieure - Indoor unit		Codice	CASK-12C	CASK-18C	
Unità Esterna - Unité extérieure - Outdoor unit		Codice	SKOV-12	SKUOV-18	
SEER/ SCOP		W/W	6,1/4,0	6,1/4,0	
Etichetta Energetica			A++/A+	A++/A+	
Alimentazione - Power Supply - Alimentation électrique		V-Hz-Fase	230 - 50 - 1		
Raffreddamento Cooling capacity Puissance frigorifique	Potenza	Nominale	W/BTU	3500 / 12000	5300 / 18000
		Max/Min	W	4220/703	6327/1054
	Assorb. elettrico	Nominale	W	1066	1599
		EER	W/W	3,28	3,31
Riscaldamento Heating capacity Puissance calorifique	Potenza	Nominale	W/BTU	4100 / 13000	5600 / 19000
		Max/Min	W	4570/762	7030/1172
	Assorb. elettrico	Nominale	W	1100	1530
		COP	W/W	3,73	3,61
Consumo in Stand-by		W	0,5	0,5	
Portata d'aria - Débit d'air - Air flow U.I.		m³/h	750	980	
Pressione sonora unità interna		dB(A)	39/33/30/26	41/35/32/29	
Potenza sonora unità interna		dB(A)	48/43/39/36	51/46/42/40	
Pressione/ Potenza sonora unità esterna		dB(A)	49/57	51/59	
Unità Interna - Unité intérieure Indoor unit	Dimensions (LxPxH)		mm	600 x 600 x 240	600 x 600 x 240
	Peso - Weight - Poids de l'unité		Kg	18	21
Metodo di regolazione			Capillare + EXV	Capillare + EXV	
Unità Esterna - Unité extérieure Outdoor unit	Dimensions (LxPxH)		mm	762 x 257 x 540	890 x 340 x 700
	Peso - Weight - Poids de l'unité		Kg	30	49
Refrigerante		Tipo	R410A	R410A	
Tubazioni frigorifere	Dimensioni - Dimensions		mm	Ø6,35 - Ø12,70	Ø6,35 - Ø12,70
			inch	1/4" - 1/2"	1/4" - 1/2"
Limiti di funzionamento		Ambiente Interno/Esterno (raffr / risc)	°C 16 ~ 31 / 18~52 / -15 ~24		



Unità Monosplit Cassette (840x 840 mm)							
Unità Interna - Unité intérieure - Indoor unit		Codice	CASK-18	CASK-24	CASK-36	CASK-48	
Unità Esterna - Unité extérieure - Outdoor unit		Codice	SKUOV-18	SKUOV-24	SKUOV-36T	SKUOV-48T	
SEER/ SCOP		W/W	6,1/4,0	6,1/4,0	6,1/4,0	5,6/3,8	
Etichetta Energetica			A++/A+	A++/A+	A++/A+	A+/A	
Alimentazione - Power Supply - Alimentation électrique		V-Hz-Fase	230 - 50 - 1		400 - 50 - 3		
Raffreddamento Cooling capacity Puissance frigorifique	Potenza	Nominale	W/BTU	5300 / 18000	7000 / 24000	10500 / 36000	14000 / 48000
		Max/Min	W	6327/1054	8440/1406	12654/2110	16872/2820
	Assorb. elettrico	Nominale	W	1599	2000	3100	4200
		EER	W/W	3,31	3,5	3,39	3,35
Riscaldamento Heating capacity Puissance calorifique	Potenza	Nominale	W/BTU	5600 / 19000	7800 / 26500	11700 / 40000	15600 / 53000
		Max/Min	W	7030/1172	9315/1552	14060/2343	18160/3105
	Assorb. elettrico	Nominale	W	1550	2100	3150	4250
		COP	W/W	3,61	3,72	3,72	3,67
Consumo in Stand-by		W	0,5	0,5	0,5	0,5	
Portata aria unità interna		m³/h	980	1200	1600	2000	
Pressione sonora unità interna		dB(A)	41/35/32/29	37/32	39/34	42/37	
Potenza sonora unità interna		dB(A)	51/46/42/40	48/43	50/44	51/48	
Pressione/ Potenza sonora unità esterna		dB(A)	51/59	55/64	58/70	60/71	
Unità interna	Dimensions (LxPxH)		mm	840 x 840 x 230	840 x 840 x 230	840 x 840 x 230	840 x 840 x 230
	Peso - Weight - Poids de l'unité		Kg	32	45	50	52
Metodo di regolazione			Valv. di esp. elettronica	Capillare + EXV			
Unità esterna	Dimensions (LxPxH)		mm	890 x 340 x 700	1048 x 340 x 950		1348 x 340 x 950
	Peso - Weight - Poids de l'unité		Kg	49	62	75	114
Refrigerante		Tipo	R410A	R410A	R410A	R410A	
Tubazioni frigorifere	Dimensioni - Dimensions		mm	Ø6,35 - Ø15,88		Ø9,52 - Ø15,88	
			inch	1/4" - 6/8"		3/8" - 5/8"	
Limiti di funzionamento		Ambiente Interno/Esterno (raffr / risc)	°C 16 ~ 31 / 18~52 / -15 ~24				

CONDIZIONI DI PROVA: Raffreddamento: Int. 27°C B.S. - Est 35°C B.S. / 24°C B.U. - Riscaldamento: Int. 20°C B.S. - Est 7°C B.S. / 6°C B.U.